SELLER TYPE

A code used to identify orders for Wholesale/Resale/UNE

1 VZ Retail
R Resale
A or C UNE
P COIN

CL FID:

Circuit Layout identifies the type of circuit

any code in this field identifies the service as a special service

Service Code Modifier (SCM):

Identifies the service grouping of a special service circuit .

ITEM	SERVICE ORDER	SORD FILED	VALUE
Dispatch	OCB in STAT section	OCB_COC	='O'
No Dispatch	N0 OCB in STAT section	OCB_COC	<>'O'
Offered Interval	Elapsed business days between the application date and due date in Header Section	APPINTV	INTERGER
Completion Interval	Elapsed business days between the application date and completion date in header section	CMPINTV	INTERGER
Status complete		STATUS	='55B'
Company services	SWO = is NF or NC in STAT section	SWO_CODE	<>'NC', 'NF'
Seller	RSID or AECN in ID CCAR section	SELLER_NAME	
ATC	Appointment type code after due date in header section	ATC	W' OR 'X'
Service Code Modifier	Position 3-4 of circuit ID in S&E section	SCM	SEE DS TABLE
Customer Missed Appointment	Follows "SD/" after due date in Header Section	CISR_MAC Company	COMPANY BEGINS WITH 'C'. CUSTOMER = SA, SR,SO, SL

SERVICE COL	DE MODIFIER (S	<u>CM)</u> TABLE FO	R DS LEVEL RI	EPORTING	
SCM - FIRST	Report Level	SCM - FIRST	Report Level	SCM - FIRST	Report Level
2 Characters	,	2 Characters	.,	2 Characters	
AB	DS0	QY	DS0	ED	DC2
CC	DS0	RC	DS0		DS3
DA	DS0	ST	DS0	EH EJ	DS3 DS3
<u> </u>	DS0	US .	DS0	EK EK	DS3
DM	DS0	WB -	DS0	FI	DS3
DP	DS0	wc	DS0	GW	DS3
DQ	DS0	WD	DS0	HD	DS3
DR	DS0	WE	DS0	HE	DS3
DS	DS0	WF	DS0	HF	DS3
DW	DS0	XA	DS0	HG	DS3
DX	DS0	XB	DS0	HH	DS3
DY	DS0	XC	DS0	HI	DS3
DZ	DS0	XD	DS0	HT	DS3
FE	DS0	XE	DS0	HZ	DS3
FF	DS0	XF	DS0	JI	DS3
GA	DS0	XG	D\$0	JJ	DS3
GB	DS0	XH	DS0	JK	DS3
GC	DS0	XI	DS0	LI	DS3
GD	DS0	XJ	DS0	LM	DS3
GE	DS0	XR	DS0	LO	DS3
GF	DS0	YG	DS0	LW	DS3
GG	DS0	YN	DS0	LX	DS3
GH	DS0			LY	DS3
Gl	D\$0			MB	DS3
GJ	DS0	AC	DS1	MD	DS3
GK	DS0	AH	DS1	ME	DS3
GL	DS0	AQ	DS1	MF	DS3
GM	DS0	AR	DS1	MG	DS3
GN	DS0	AS	DS1	MH	DS3
GO	DS0	CH	DS1	МІ	DS3
GP	DS0	DB	DS1	MJ	DS3
GQ	DS0	DF	DS1	MK	DS3
GR	DS0	DG	DS1	MM	DS3
GS	DS0	DH	DS1	MP	DS3
GT	DS0	FL	DS1	OA OA	DS3
GU	DS0	HC	DS1	OB	DS3
GV	DS0	HJ	DS1	OD	DS3
GZ	DS0	HK	DS1	OE OF	DS3
HA	DS0	HL	DS1		DS3
HB HP	DS0 DS0	HN HU	DS1 DS1	OG QC	DS3 DS3
HQ HQ	DS0 DS0	HX HX	DS1 DS1	QH QH	DS3
HR	DS0	IP	DS1	QI	DS3
HS	DS0 DS0	JE	DS1 DS1	TV 1	DS3
HW	DS0	QA QA	DS1	TZ	DS3
HY	DS0	QG	DS1	VR	DS3
A	DS0	SY	DS1	YH	DS3
iB	DS0	UF	DS1 DS1	YI	DS3
ID I	DS0	UH	DS1	11	טטט
PC	DS0	UM	DS1		
QB	DS0	VS	DS1		
QD QD	DS0	VW	DS1	<u> </u>	
QE QE	DS0	VX	DS1		
QJ	DS0	- VŶ	DS1		
QK	DS0	YB	DS1		
QL	DS0	ID	ופע		
QR	DS0				
QS	DS0				
<u> </u>	D30		1		

APPENDIX C

Log files - the daily files produced by the robots that include the records for all of the requests issued during the report period and the resulting dispositions and response times. There are three types of log files that are used to create the text files:

```
rr xxx.loa*
rrr_xxx.dlg
rrr_xxx.dtm
```

*rr and rrr = the robot designation and xxx = the cycle date

The EnView application creates the log files for the OSS. A REXX program creates the log files on the DCAS side. Currently the log files are stored on the robots for five days; however, they are FTP'd (File Transfer Protocol) daily to multiple locations including the EnView server for the North where they remain until written to compact disk. Once written to compact disk, copies are maintained by EnView and Wholesale Metrics personnel. The log files are automatically FTP'd to the EnView server each morning.

Text files - Text files are produced from the log files that are FTP'd daily from the EnView server to the Metrics PC for analysis and reporting. Daily average response times are calculated by the EnView program and are included in the text files. The following text files are FTP'd daily:

```
All of the requests issued during the report period.
N_xxx.rec*
N_xxx.rep
                Average response times by hour and day for the report period.
```

N_xxx.sum Hourly counts by transaction type for the 24-hour period

All of the requests issued during the 24-hour period including response times. N_xxx.all

*xxx=the cycle date

Excel workbook - the format for VZ internal daily distribution and reporting of the official response time results. Monthly average response times are calculated in the Excel workbook.

The following Excel workbook is updated and distributed internally each business day: Sentl~no.xls

Transactions included in the EnView text files:

BOSS1_T_BCO	OSS – BOSS Product and Services Availability Simple Business
BOSS1_T_CCO	OSS – BOSS Product and Services Availability Complex Business
BOSS1_T_CSR	OSS – BOSS Customer Service Record
BOSS1_T_RCO	OSS – BOSS Product and Services Availability Residence
BOSS2_T_CSR (DSS – BOSS Customer Service Record
DCAS68_ADR	DCAS – Address Validation
DCAS68_ADRTNR	DCAS – Telephone Number Restore
DCAS68_ADRTNS	DCAS – Telephone Number Select
DCAS68_CSR	DCAS – Customer Service Record
DCAS68_DDA	DCAS – Due Data Availability
DCAS68_PSA	DCAS – Product and Services Availability
PREMIS_NE_T_REQPR	EM OSS – PREMIS Address Validation
PREMIS_NE_REQTNR	OSS – PREMIS Telephone Number Restore
PREMIS_NE_REQTNS	OSS – PREMIS Telephone Number Select
SOP_T_WLU	OSS – SOP Due Date Availability
NAK No Acknowledgen	nent – the request file contains an error (bad transmission) as received by the
DCAS host (DCAS only)	

е DCAS host (DCAS only)

SEM - System Error Message - the request file contains a syntax mistake or OSS is unavailable (DCAS only)

ACK - Acknowledgement - the request file is accepted by the DCAS host (DCAS only)

TIMEOUT - neither a SEM (DCAS) nor an indication of a successful response is received by the robot within a predetermined amount of time. (DCAS and OSS)

Appendix C Pre-Ordering EnView Additional Details (continued)

Timeouts for the DCAS transactions are set at 60 seconds.

The following transactions and response time differences are measured and reported for PreOrder response times:

Customer Service Record DCAS68_CSR BOSS1_T_CSR

Difference

Address Validation

DCAS68_ADR PREMIS_NE_T_REQPREM Difference

Due Date Availability

DCAS68_DDA SOP_T_WLU Difference

Telephone Number Select

DCAS68_ADRTNS PREMIS_NE_REQTNS Difference

Product and Services Availability

DCAS68_PSA BOSS1_T_BCO Difference

ENVIEW PROCESS - NOTES:

There are currently two robots that log into applications and execute transactions for the PreOrder response time measurement process. The EnView process and the resulting response times are common to the VZ North footprint due to the commonality of the interface. Transactions are executed through customizable scripts created for each application based on replications of actual transactions of a Verizon service representative using the OSS and of a CLEC representative accessing the OSS through the DCAS interface. The ROBOT creates log records that show whether the transaction was successful or failed, and records transaction response times.

The robot sends the DCAS transactions to the same web server that the customers use. There is no difference between the processing of the EnView transactions and those submitted by the CLECs through the interface and back-end applications. Corresponding transactions are sent directly by EnView to the OSS as well.

The process is active on a 7 day by 24-hour basis. However, only those transactions included in the report period as defined above are recorded and documented as PreOrder response times. Data from the EnView robot log files is processed daily and average response times by hour and by day for each of the above transactions is calculated and included in the text files that are used for input to the Excel workbooks. These daily response times are subsequently averaged by month in the Excel workbook.

Appendix C Pre-Ordering EnView Additional Details (continued)

The resulting averages and the differences between the corresponding retail and wholesale average response times are reported and distributed daily.

NAKs, SEMs, and Timeouts are not included in these calculations. They are removed from the queue and reported separately in the text files. ACKs, by themselves, are also not included in the calculations but the acknowledgement process is part of the overall process for a successful transaction. Daily average response times as received in the EnView text files are reported "as is" in the Excel workbook with the exception of Telephone Number Select for OSS. It is not possible to do a Telephone Number Select transaction in DCAS without including an Address Validation. However, in the OSS these transactions are separate and manual effort is required to update the service rep's screen in between actions.

In order to make a like for like comparison between DCAS and the OSS an adjustment is made to the response times prior to calculating the DCAS and OSS response time differences. The daily average response time for the PREMIS Address Validation transaction is combined with the response time for the PREMIS Telephone Number Select transaction. Monthly average response times and differences are calculated and reported at the close of each month. The monthly average is calculated for each transaction type by averaging all of the daily average response times. Monthly results include response times for each of the PreOrder transaction types and a Non-CSR Combined average response time for the non-CSR transactions. This is calculated by averaging each of the monthly averages for the non-CSR transactions. Transaction count weighting factors are not included in the averaging process.

APPENDIX D

APPENDIX E

LOCAL NUMBER PORTABILITY/HOT-CUT

LNP/Hot-Cut Process

The CLEC sends an LSR to VZ for a loop hot-cut with LNP. VZ returns a FOC to the CLEC with the date and time for the cutover. VZ also sends a message via the SOA (service order activation system) to NPAC indicating that the affected telephone number will be made available for LNP activation. This message creates a subscription version in the NPAC. VZ sends the message to NPAC at the same time that the service order is issued. This is mechanized for all orders except DID/CTX. If the CLEC uses DCAS or other mechanized interface for LSR, the FOC, (or more correctly the LSC), will be returned to the CLEC the same time the service order is issued and the message goes to the NPAC. If a paper LSR is used, VZ NY will send the LSC back to the CLEC after VZ NY issues the order.

The first company that sends the subscription version to NPAC starts the NPAC concurrence timers. Since VZ's internal service order generates the FOC and NPAC create message at the same time, VZ's activity starts the NPAC timers. This process is outlined in the industry agreed upon NANC LNP Process Flows. The CLEC/new service provider has 18 hours to enter their subscription from the time the VZ NY subscription version is sent to the NPAC. NPAC hours are from 7 am to 7 pm Central Time excluding weekends and holidays. If the CLEC does not enter a subscription within the 18 hours, then their subscription will be canceled. This timing issue and NPAC subscription version cancellation was a problem for many CLECS when they first started porting with the LNP process.

Upon receipt of the FOC, the CLEC sends a message to NPAC specifying the date and time for the activation of LNP. Alternatively, the CLEC may specify only the date initially and, when they are ready to port, a second message to NPAC to activate LNP in real time. VZ has observed that most CLECs' initial subscription entered into NPAC via SOA contains the date due only. On the date due the CLEC will send an ACTIVATE message via SOA to NPAC when they are ready to port the Verizon number. Two basic scenarios may occur.

Scenario 1 - PORT OUT of the Verizon number associated with an Unbundled Loop HOT CUT conversion:

Prior to the due date, the VZ Regional CLEC Co-ordination Center (RCCC) will arrange with internal VZ personnel to have the cable pairs moved on the agreed upon due date at specific time known as the frame due time (FDT). In addition, at least one day prior to the due date VZ will install a 10 digit unconditional trigger on the VZ line (during the porting process, it is VZ's policy to place the 10 digit trigger on all non-Centrex/DID numbers to direct all calls to the number being ported to be queried at the LNP data base before any call termination is attempted). For all HOT CUTS (with or without LNP or INP) of unbundled loops, the CLEC is required to have dial tone at their collocation 48 hours before the DD. The RCCC will verify dialtone 24 hours before the cutover and notify the CLEC of any problems found. On the due date, the RCCC will call the CLEC 1 hour before the scheduled cutover time to ensure that both parties are ready. If the CLEC indicates that the port should proceed. VZ will cut the loop at the scheduled time and report the completion to the CLEC within 60 minutes. Upon notification of the completion, the CLEC would send a notice to NPAC to activate LNP in real time, if the time was not initially specified. As long as a trigger has been placed on the Verizon line, this PORT OUT is under the total control of the CLEC. However, the line should be ported at the FDT (Frame Due Time) of the Unbundled Loop conversion to prevent any service interruptions.

Scenario 2 - <u>PORT OUT of the Verizon number NOT associated with an Unbundled Loop HOT CUT:</u> VZ will issue service orders to place the 10-digit trigger on the line at least one day prior to the date due and to remove the end user telephone number translation from the VZ switch at 11:59 pm using the FDT. For informational purposes the CLEC requested work completion time will be carried on the VZ service order. At the same time the service orders are issued, VZ will send the FOC to the CLEC and the create subscription version to the NPAC. The NPAC 18-hour timers will start at this point. Since no hotcut is involved, once the 10 digit trigger is added to the VZ telephone number, the CLEC

has control of the porting activity and there should be no customer service interruption if the CLEC completes their work by 11:59pm on the confirmed due date. If the 10 digit trigger is not applied because the VZ account is Centrex or DID, then the FDT would govern the porting out activity and VZ will handle in the same manner as a hotcut.

Note that triggers can be placed on all lines with OE (Office equipment). Centrex and DID service require coordination between the CLEC and the RCCC at the FDT. VZ places the 10-digit trigger on all non-Centrex/DID porting orders. The 10-digit trigger enables intraswitch call origination and donor switch query calls to be routed to the CLEC's switch even if the line is not disconnected from the switch. This

will happen only if the CLEC has updated the LNP database via an NPAC activation message. Basically the 10 digit trigger mitigates the need to closely co-ordinate the disconnect of the line with the CLEC. VZ activates the 10 digit trigger at least 1 day prior to the porting due date; it is deactivated when the TN translations are removed from the switch. The 10-digit trigger has no other network purpose.

On all ports without a loop and with a trigger, the VZ service order will carry

a FDT of 11:59 PM. The trigger will not be deactivated until that time. Therefore, the CLEC is able to use the full day of the due date to complete their work activities (switch translations, loop installs, NPAC activate, etc.) before the VZ line is disconnected from the switch.

APPENDIX F

ENHANCED 911 DATABASE UPDATES

Background:

The E911 database identifies the street address associated with each telephone number, thus enabling PSAPs to automatically identify an emergency caller's location, if the emergency caller is unable to communicate this information verbally.

The E911 database is owned and maintained by VZ in those counties where VZ is the incumbent telephone company or has been contracted by the municipality or state to be the lead telephone company or database administrator. However, the company that provides dial tone to a telephone number is responsible for updating the E911 database when there is service order activity. VZ is responsible for updating the E911 database for their own customers, for customers of CLECs served by resale of VZ's local service or by VZ's UNEs. CLECs are responsible for updating the E911 database for customers that receive dial tone via CLECs' switching equipment.

The E911 database is updated by means of an electronic interface. VZ updates the E911 database once each evening from the VZ service order systems through a file transfer protocol. Facilities based CLECs use PS/ALI and have the opportunity to upload their records 10 times per day. VZ developed this interface for PBX's and subsequently it is available for use by CLECs so that they can update the E911 database when they provide the dial tone.

When VZ or a CLEC attempts to update the E911 database, the address is compared against a range of permissible street addresses contained in the Master Street Address Guide (MSAG). The MSAG is compiled by the E911 municipalities and consists of address information provided by each of the E911 municipalities. Thus, the MSAG is only as accurate as the information supplied by the municipalities.

If the E911 database cannot accept the update, either because of a discrepancy with MSAG or for some other reason, the E911 database generates an error message that identifies the nature of the problem. The Telephone Company attempting to update the database must then correct the problem and resubmit the information.

Local Number Portability (LNP) requires additional steps pursuant to procedures developed by the National Emergency Number Association called "NENA Recommended Standards for Service Provider Local Number Portability." The donor company must issue an "unlock" order to the E911 database to make the telephone number available to the recipient company, and the recipient company must issue a "migrate" order to the E911 database to identify the new dial tone provider. The E911 database does not have the updated customer's carrier identification code until both orders are issued in the proper sequence. Nevertheless, the customer's E911 record is present in the database and the customer's access to E911 service is unaffected. The responsibilities and procedures for updating the E911 database are described in VZ's CLEC Handbook and E911 PS/ALI Guide. Both documents are available to the public at VZ's website.

APPENDIX G

8.8 (Repair) Disposition Codes

Disposition Codes exist to identify defects in equipment or facilities and customer error or misuse of Telephone Company (TELCO) and Customer Equipment.

8.8.1 DISPOSITION CODES NORTH

Disposition Code Table		
Disposition Code Trouble was found in:		
03xx	Verizon Wire	
0371	Protector	
0372	Ground Wire	
0373	Radio Suppressor	
0381/0382	Aerial Drop Wire	
0383/0384	Buried Drop Wire	
0385	Block/Bridle Wire	
0391-97	Network Interface Device	
04xx	Verizon Cable Plant	
040x	Pair Transferred	
041x	Sheath, Case, End Cap, etc.	
042x	Closure/Splice Case	
043x	Terminal	
044x	Fiber Optic Cable	
045x	Fiber Termination	
046x	Fiber Splice	
047x	Pair Gain Analog	
048x	Pair Gain Digital	
049x	Cable Misc. (Pole, Guy, Trench, etc.)	
05xx	Verizon Central Office	
051x	Switch	
052x	Translations (Software)	
053/054x	Frame (Hardware)	
055x	Power Equipment	
056x	Central Office Misc. Equipment	

Appendix G Repair Disposition Codes

Disposition Code Table		
Disposition Code	Trouble was found in:	
057x	Central Office Special Services Equipment	
058x	Central Office Voice Mail Service Equipment	
12xx	CPE (Customer Premises Equipment)	
1220	Dispatched Out on a demand dispatch/trouble proven into CPE/IDC applies.	
1232	Dispatched In/trouble proven in CLEC portion of circuit/IDC applies.	
1235	Demand dispatch for cooperative test IDC applies.	
1239	Dispatch Out on a demand dispatch/proven into CLEC portion of circuit/IDC applies.	
1239	Dispatch Out on a demand dispatch/no access to premises/CNR applies.	
1296	Dispatched In/trouble not found within Verizon's Central Office/IDC applies.	

8.9.1 CAUSE CODE TABLE - NORTH

The Cause Code describes the trouble's cause.

Cause Code Table		
Cause Code	Trouble was caused by	
1XX	Employee	
2XX	Non-employee	
3XX	Plant Equipment	
4XX	Weather	
5XX	Other	
6XX	Miscellaneous	
600	Unknown	
610	Came Clear	
698	CPE Trouble – IDC Incurred	
699	CPE Trouble – Auto Generated IDC Incurred	

APPENDIX H

VERIZON PRODUCT	ORDERING SCENARIO	NORTH FLOWTHROUGH
Resale		
	New Connect: business or residence, straight line main listing	Level 5
	New Connect with hunting	Level 5, Series & circular only
	As Specified, Add or Drop Line with hunting changes	Level 5
	As-Is Residence and Business	Level 5
	As-Is w/Changes: involving Freeze PIC, PIC/ LPIC Change, Customized Routing, & Blocking	Level 5
	As Specified Full Migration	Level 5
	As Specified Partial Migration	Level 5
	As Specified drop a line, not the main	Level 5
	Post Migration Delete Account (disconnect of account)	Level 5
	Post Migration Change - Add or Drop Features (no change feature detail) This includes ADD of features on inscope list and DROP of any feature with the exception of Distinctive Ringing	Level 5
	Post Migration New/Add Lines	Level 5
	Post Migration Disconnect Lines	Level 5
	Post Migration PIC Change	Level 5
	Outside Moves (includes same or different TNs, same or different due dates, and dual service)	Level 5

VERIZON PRODUCT	ORDERING SCENARIO	NORTH FLOWTHROUGH
UNE Platform		
	New Connect: business or residence, straight line main listing	Level 5
	As Specified, Add or Drop Line without hunting changes	Level 5
	As-Is Residence or Business	Level 5
	As-Is w/Changes: involving Freeze PIC, PIC/ LPIC Change, Customized Routing, & Blocking	Level 5
	As Specified (no disconnect of lines)	Level 5
	As Specified Full Migration	Level 5
	As Specified drop a line, not the main	Level 5
	Post Migration Delete Account (disconnect of account)	Level 5
	Post Migration Change - Add or Drop Features (no change feature detail) This includes ADD of features on inscope list and DROP of any feature with the exception of Distinctive Ringing	Level 5
	Post Migration New/Add Lines	Level 5
	Post Migration Disconnect Lines	Level 5
	Post Migration PIC Change	Level 5
	Post Migration SNP Deny (one-way & two-way)	Level 5
	Post Migration SNP Restore (one-way & two-way)	Level 5
	Post Migration Seasonal Suspend	Level 5
	Post Migration Seasonal Restore	Level 5
	Post Migration Short-Term	Level 5
	Post Migration TN Change (Non-BTN)	Level 5
	Resale to Platform Full Migration	Level 5
Basic 2 Wire Loop		
	New Connect: 1-9 loops	Level 5
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
	Post Migration New/Add Loops: 1-9 loops	Level 5
	Post Migration Delete Loops	Level 5
Premium 2 Wire Loop		
	New Connect: 1-9 loops	Level 5
	Post Migration New/Add Loops: 1-9 loops	Level 5
	Post Migration Delete Loops	Level 5
······································		
CSS 2 Wire Loop	Post Migration Delete Loops	Level 5
Basic 2 Wire M		
Loop		
	Post Migration Delete Loops	Level 5

PRODUCT	ORDERING SCENARIO	NORTH FLOWTHROUGH
INP		
	Delete INP Arrangement Only	Level 5
Loon w/ND No		
Loop w/NP - No listing (LNP)		
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
Standalone Number Portability (LNP)	er	
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
Loop W/New /Cnai	nge Main Straight Line Listing	
	New Connect: 1- 9 loops	Level 5
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
	d w/ New Main Straight Line Listing	
Platform combined	w we want straight Line Listing	
Platform combined	New Connect	Level 5
Platform combined		Level 5 Level 5
	New Connect	
	New Connect Post Migration (additional listings only) pined w/Main Straight Line Listing Change	Level 5
	New Connect Post Migration (additional listings only) Dined w/Main Straight Line Listing Change Full Migration	Level 5
	New Connect Post Migration (additional listings only) pined w/Main Straight Line Listing Change	Level 5
Loop w/LNP comb	New Connect Post Migration (additional listings only) Dined w/Main Straight Line Listing Change Full Migration	Level 5
Loop w/LNP comb	New Connect Post Migration (additional listings only) Dined w/Main Straight Line Listing Change Full Migration Partial Migration (taking BTN = Level 2)	Level 5

	ORDERING SCENARIO	NORTH FLOWTHROUGH
PRODUCT Loop w/LNP comb	ined w/Listing As Is (No Change)	TLOWITROUGH
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
Platform combined		
w/Listing As Is		
	As-Is	Level 5
	As-Is w/Changes	Level 5
	As Specified (Full Migration)	Level 5
	Full Migration (No DI Form is required)	Lavel 5
	Full Migration (No DL Form is required) Partial Migration (taking RTN = Level 2)	Level 5
	Full Migration (No DL Form is required) Partial Migration (taking BTN = Level 2)	Level 5 Level 5
Platform combined		
Platform combined	Partial Migration (taking BTN = Level 2)	
Platform combined	Partial Migration (taking BTN = Level 2) w/Delete Additional Listing	Level 5
	Partial Migration (taking BTN = Level 2) w/Delete Additional Listing	Level 5
Standalone	Partial Migration (taking BTN = Level 2) w/Delete Additional Listing Post Migration	Level 5
Standalone	Partial Migration (taking BTN = Level 2) w/Delete Additional Listing	Level 5 Level 5
Standalone	Partial Migration (taking BTN = Level 2) w/Delete Additional Listing Post Migration UNE New Straight Line Listing, main listing	Level 5 Level 5 Level 5

APPENDIX I PART 1



Telecom Industry Services

CLEC Interconnection Trunking Forecast Guide

September 2000

Introduction

Introduction	The purpose of this CLEC Interconnection Trunking Forecast Guide and attached documents is to provide guidelines for the formats and language to be used in exchanges of forecast information between CLECs and Verizon. These guidelines in no way supersede any established or future Interconnection Agreements between Verizon and individual CLECs. The Verizon CLEC Interconnection Trunking Forecast Process is an interactive planning process between the CLECs and Verizon. This recommended process represents a work in progress and may be modified as appropriate.
Initial Implementation	The Trunk Forecasting Process was implemented to meet the requirements of Verizon's forecasting and capital budget process.
Evaluation	The Trunk Forecasting Process will be monitored by Verizon with input from all CLECs to evaluate the success of the forecast process.

CLEC Interconnection Trunking Forecast Process

Why Do We Need	1. To ensure that trunk groups do not exceed their design blocking thresholds.
Forecasts?	 To ensure adequate infrastructure planning to meet customer service requirements within standard intervals. CLECs and Verizon analyze forecast information in order to: Design optimum network infrastructure. Prioritize and allocate limited capital funds for next year's switching, transport and OSS projects. Allocate expense budgets and human resources.
Impact of	Unforecasted Demand Forces:
Unforecasted	Blockage that exceeds design blocking thresholds.
Demand	 Redesign of infrastructure network in various areas.
	Sub-optimization of planned aggregate infrastructure.
	Reallocation of funds for infrastructure.
	 Reprioritizing, rescheduling, or cancellation of planned projects.
	Reallocation of human resources.
The state of the s	